

DUGARD

Since 1939

Dugard Eagle Gap Bed Manual Lathes



Dugard Eagle 1660 Gap Bed Manual Lathe

Machine Specification	
Maximum Swing over Bed	400mm
Max Swing over cross slide	210mm
Gap Bed - Max Swing	590mm
Distance Between Centres	1500mm
Width of Bed	300mm
Spindle Nose	D1-6
Spindle Bore	58mm (1660B 80mm)
Spindle Speeds (12 Steps)	50-2000rpm
Metric Threads	0.5-7mm (21 types)
Inch threads	4-56 T.P.I (32 types)
Module Threads	0.5-7mm (21 types)
Diametrical Pitch Threads	4-56 D.P (32 types)
Longitudinal Feeds Range	0.059-0.831mm (0.002-.0033in)
Cross Feeds Range	0.019-0.271mm (0.001-0.011in)
Main Motor Power	5.5kW (7.5HP)
Weight	2200 Kgs

Standard Equipment
Two Axis D.R.O.
Three & Four Jaw Chucks 1660 (10"- 3 Jaw & 12"- 4 Jaw) 1660B (10"- 3 Jaw & 12"- 4Jaw)
Quick Change Tool Post + 4 Tool holders
Face Plate
Steady Rest
Coolant System
Lighting
Covered Leadscrew
Centres, Reduction Sleeves, Wrenches, Oil Gun
Collet Chuck

European headquarters for Dugard CNC Machine Tools

DUGARD.com

www.dugard.com email: sales@dugard.co.uk tel: +44 (0)1273 732286